



Attribute Definitions For Individual Data

Version 1.2.0

4 May 2006

1 Introduction

These schema definitions are intended to facilitate information exchange among European, and possibly international, academic and research institutions.

In its current version, the SCHAC schemas are not oriented to any particular technology. They define a set of attributes to describe individuals in the academic and research institutions. An appropriate LDAP profile is included as an appendix of this document. An XML profile will be defined in other document.

These definitions assume that other attributes describing individuals are already available and properly coded, according with the following standards:

- The **eduPerson** schema v. 200312, as defined at <http://www.educause.edu/eduperson/>
- The **person** schema, as defined by X.521 (2001)
- The **organizationalPerson** schema, as defined by X.521 (2001)
- The **inetOrgPerson** schema, as defined by RFC 2798

2 Attribute Meta-Information And Notation

For all attributes, the following metadata is defined:

Name	A label used to identify and distinguish one attribute from another
Description	A short description of the attribute
Format	The syntax for the representation of the attribute's values
# of values	<ul style="list-style-type: none"> ● Single Only one value is permitted for describing a given individual ● Multi An indefinite number of values can be used
References	Additional information used to clarify some properties of attributes like format, description or # of values
RFC 2252 definition	Lightweight Directory Access Protocol (v3): Attribute Syntax Definitions
Examples	Example of values used within the attribute

3 Attribute Classification

The attributes considered in this document are designed to contain information specifically about people. It is helpful to consider this information within broad categories. The ten categories used in this document have been collected from the NMI LocalDomainPerson survey and discussions with the International Schema Archives (Feb, 2004). The categories are:

- Personal Characteristics
- Contact / Local Information
- Student Information
- Employee Information
- Linkage Identifiers / Foreign Keys
- Entry Metadata / Administration Information
- Security Attributes and Keys
- Confidentiality / Attribute Release (Visibility)
- Authorization, Entitlements
- Group-related Attributes

A detailed description of these categories can found in the document: *Higher-Education Person: A Comparative Analysis of Collaborative Public LDAP Person Object Classes in Higher-Education* <[draft-internet2-mace-dir-higher-ed-person-analysis-06.htm](#)>, <<http://middleware.internet2.edu/dir/docs/draft-internet2-mace-dir-higher-ed-person-analysis-latest.htm>>

4 Attributes Defined By SCHAC

4.1 Personal Characteristics

Personal characteristics describe the individual person represented by the entry.

4.1.1 schacMotherTongue

Name	schacMotherTongue
Description	Is the language a person learns first. Correspondingly, the person is called a native speaker of the language. Usually a child learns the basics of their first language from their family.
Format	See RFC 3066 Tags for the Identification of Languages
# of values	Single
References	<ul style="list-style-type: none"> ● ISO 639 - Language Codes ● RFC 2798 - Definition of the inetOrgPerson LDAP Object Class ● RFC 3066 - Tags for the Identification of Languages
RFC 2252 definition	(schacAttributeType:1 NAME 'schacMotherTongue' DESC 'RFC 3066 code for preferred language of communication' EQUALITY caseExactMatch SINGLE-VALUE SYNTAX 1.3.6.1.4.1.1466.115.121.1.15)
Examples	schacMotherTongue = fr schacMotherTongue = es-ES

4.1.2 schacGender

Name	schacGender
Description	The state of being male or female. The gender attribute specifies the legal gender of the subject it is associated with. "Either of the two groups that people, animals and plants are divided into according to their function of producing young" (Oxford Advanced Learner's Dictionary)
Format	<ul style="list-style-type: none"> • 0 Not known • 1 Male • 2 Female • 9 Not specified
# of values	Single
References	<ul style="list-style-type: none"> ● RFC 2985 - PKCS #9: Selected Object Classes and Attribute Types Version 2.0. Sections 5.2.6, B.3.10 ● ISO 5218 - Information interchange -- Representation of human sexes. The standard ISO 5218 defines the representation of the human sexes by a numeric digital code. It was created by the Data Management and Interchange Technical Committee and proposed in November 1976
RFC 2252 definition	(schacAttributeType:2 NAME 'schacGender' DESC 'Representation of human sex (see ISO 5218)' EQUALITY integerMatch SINGLE-VALUE SYNTAX 1.3.6.1.4.1.1466.115.121.1.27)
Examples	schacGender = 2

4.1.3 schacDateOfBirth

Name	schacDateOfBirth
Description	The date of birth for the subject it is associated with
Format	Numeric value YYYYMMDD, using 4 digits for year, 2 digits for month and 2 digits for day as described in RFC 3339 'Date and Time on the Internet: Timestamps' as reference using the 'full-date' format from paragraph 5.6 but without the dashes.
# of values	Single
References	<ul style="list-style-type: none"> ● RFC 2985 - PKCS #9: Selected Object Classes and Attribute Types Version 2.0. Sections 5.2.4, B.3.8 ● RFC 3339 - Date and Time on the Internet: Timestamps. 'Date and Time on the Internet: Timestamps' as reference using the 'full-date' format from paragraph 5.6 but without the dashes ● ISO 8601 - Data elements and interchange formats - Information interchange - Representation of dates and times
RFC 2252 definition	(schacAttributeType:3 NAME 'schacDateOfBirth' DESC 'Date of birth (format YYYYMMDD, only numeric chars)' EQUALITY numericStringMatch ORDERING numericStringOrderingMatch SUBSTR numericStringSubstringsMatch SINGLE-VALUE SYNTAX 1.3.6.1.4.1.1466.115.121.1.36)
Examples	schacDateOfBirth = 19660412

4.1.4 schacPlaceOfBirth

Name	schacPlaceOfBirth
Description	The schacPlaceOfBirth attribute specifies the place of birth for the subject it is associated with.
Format	Free string
# of values	Single
References	<ul style="list-style-type: none"> ● RFC 2985 - PKCS #9: Selected Object Classes and Attribute Types Version 2.0. Sections 5.2.5, B.3.9
RFC 2252 definition	(schacAttributeType:4 NAME 'schacPlaceOfBirth' DESC 'Birth place of a person' EQUALITY caseIgnoreMatch ORDERING caseIgnoreOrderingMatch SUBSTR caseIgnoreSubstringsMatch SINGLE-VALUE SYNTAX 1.3.6.1.4.1.1466.115.121.1.15)
Examples	schacPlaceOfBirth = Algeciras, Spain

4.1.5 schacCountryOfCitizenship

Name	schacCountryOfCitizenship
Description	The schacCountryOfCitizenship attribute specifies the (claimed) countries of citizenship for the subject it is associated with.
Format	Two-letter country acronym in accordance with ISO 3166.
# of values	Multi
References	<ul style="list-style-type: none"> ● RFC 2985 - PKCS #9: Selected Object Classes and Attribute Types Version 2.0. Sections 5.2.7, B.3.11 ● ISO 3166 - Codes for the representation of names of countries and their subdivisions
RFC 2252 definition	(schacAttributeType:5 NAME 'schacCountryOfCitizenship' DESC 'Country of citizenship of a person. Format two-letter acronym according to ISO 3166' EQUALITY caseIgnoreMatch SYNTAX 1.3.6.1.4.1.1466.115.121.1.15)
Examples	schacCountryOfCitizenship = es

4.1.6 schacSn1

Name	schacSn1
Description	First surname of a person ("the surname" in international terms). schacSn1 would contain whatever values the described person thinks they should contain. Splitting shall be done by humans. That means that, when filling a SCHAC-based description that allows the use of schacSn1 and schacSn2, the administrators must ask for 1st surname and 2nd surname (if applicable) as well as they do for givenName, surname, etc.
Format	Free string
# of values	Multi
RFC 2252 definition	(schacAttributeType:6 NAME 'schacSn1' DESC 'First surname of a person' EQUALITY caseIgnoreMatch ORDERING caseIgnoreOrderingMatch SUBSTR caseIgnoreSubstringsMatch SYNTAX 1.3.6.1.4.1.1466.115.121.1.15)
Examples	In Spain, if <i>sn = Lopez de la Moraleda y de Las Altas Alcornias</i> and that person uses <i>Lopez de la Moraleda</i> as the first component of the surname we can write: schacSn1 = Lopez de la Moraleda In Poland, if <i>sn = Gorecka-Wolniewicz</i> and we decide to use the national convention for the sn attribute, we can write: schacSn1 = Wolniewicz

4.1.7 schacSn2

Name	schacSn2
Description	Second surname of a person (how this is assigned is a local matter). schacSn2 would contain whatever values the described person thinks they should contain. Splitting shall be done by humans. That means that, when filling a SCHAC-based description that allows the use of schacSn1 and schacSn2, the administrators must ask for 1st surname and 2nd surname (if applicable) as well as they do for givenName, surname, etc.
Format	Free string
# of values	Multi
RFC 2252 definition	(schacAttributeType:7 NAME 'schacSn2' DESC 'Second surname of a person' EQUALITY caseIgnoreMatch ORDERING caseIgnoreOrderingMatch SUBSTR caseIgnoreSubstringsMatch SYNTAX 1.3.6.1.4.1.1466.115.121.1.15)
Examples	In Spain, if <i>sn = Lopez de la Moraleda y de Las Altas Alcornias</i> and that person uses <i>de Las Altas Alcornias</i> as the second component of the surname we can write: schacSn2 = de Las Altas Alcornias In Poland, if <i>sn = Gorecka-Wolniewicz</i> and we decide to use the national convention for the sn attribute, we can write: schacSn2 = Gorecka

4.1.8 schacPersonalTitle

Name	schacPersonalTitle
Description	The Personal Title attribute type specifies a personal title or salutation for a person. Examples of personal titles are "Ms", "Dr", "Prof", "Rev", "Sr".
Format	Free format string
# of values	Single
References	<ul style="list-style-type: none"> ● RFC1274 - The COSINE and Internet X.500 Schema personal title Sections 9.3.30
RFC 2252 definition	(schacAttributeType:8 NAME 'schacPersonalTitle' DESC 'RFC1274: personal title' EQUALITY caseIgnoreMatch SUBSTR caseIgnoreSubstringsMatch SYNTAX 1.3.6.1.4.1.1466.115.121.1.15)
Examples	schacPersonalTitle = Prof

4.2 Contact / Location Information

Higher education's established history of openness and collaboration gives rise to the use of institutional directories as a primary means of locating and contacting potential collaborators and other persons-of-interest at peer institutions.

4.2.1 schacHomeOrganization

Name	schacHomeOrganization
Description	Specifies a person's home organization using the domain name of the organization
Format	Domain name according to RFC 1035
# of values	Single
References	<ul style="list-style-type: none"> ● RFC 1035 - Domain names - implementation and specification
RFC 2252 definition	(schacAttributeType:9 NAME 'schacHomeOrganization' DESC 'Domain name of the home organization' EQUALITY caseIgnoreMatch SUBSTR caseIgnoreSubstringsMatch SINGLE-VALUE SYNTAX 1.3.6.1.4.1.1466.115.121.1.26)
Examples	schacHomeOrganization = tut.fi

4.2.2 schacHomeOrganizationType

Name	schacHomeOrganizationType
Description	Type of a Home Organization
Format	urn:mace:terena.org:schac:homeOrgType:<country-code>:<string> <ul style="list-style-type: none"> ● The <country-code> must be a valid two-letter ISO 3166 country code identifier, and assigned by the TERENA URN Registry for this attribute at http://www.terena.nl/registry/terena.org/schac/homeOrgType ● <string> from a nationally controlled vocabulary, published through the URI identified at the above mentioned TERENA URN registry.
# of values	Single
References	<ul style="list-style-type: none"> ● RFC 2141 - URN Syntax ● ISO 3166 - Codes for the representation of names of countries and their subdivisions ● TERENA URN Registry: http://www.terena.nl/registry/terena.org/
RFC 2252 definition	(schacAttributeType:10 NAME 'schacHomeOrganizationType' DESC 'Type of the home organization' EQUALITY caseIgnoreMatch SINGLE-VALUE SYNTAX 1.3.6.1.4.1.1466.115.121.1.15)
Examples	schacHomeOrganizationType = urn:mace:terena.org:schac:homeOrgType:ch:vho schacHomeOrganizationType = urn:mace:terena.org:schac:homeOrgType:es:opi

4.2.3 schacCountryOfResidence

Name	schacCountryOfResidence
Description	The schacCountryOfResidence attribute specifies the (claimed) country of residence for the subject is associated with.
Format	Two-letter country acronym in accordance with ISO 3166 country code identifier.
# of values	Multi
References	<ul style="list-style-type: none"> ● RFC 2985 - PKCS #9: Selected Object Classes and Attribute Types Version 2.0. Sections 5.2.8, B.3.12 ● ISO 3166 - Codes for the representation of names of countries and their subdivisions
RFC 2252 definition	(schacAttributeType:11 NAME 'schacCountryOfResidence' DESC 'Country of citizenship of a person. Format two-letter acronym according to ISO 3166' EQUALITY caseIgnoreMatch SYNTAX 1.3.6.1.4.1.1466.115.121.1.15)
Examples	schacCountryOfResidence = es

4.2.4 schacUserPresenceID

Name	schacUserPresenceID
Description	To store a set of values related to network presence protocols
Format	URI
# of values	Multi
References	<ul style="list-style-type: none"> ● RFC 2396 - Uniform Resource Identifiers (URI): Generic Syntax ● RFC 3508 - H.323 URL Schema ● RFC 3261 - SIP: Session Initiation Protocol
RFC 2252 definition	(schacAttributeType:12 NAME 'schacUserPresenceID' DESC 'Used to store a set of values related to the network presence' EQUALITY caseExactMatch SUBSTR caseExactSubstringsMatch SYNTAX 1.3.6.1.4.1.1466.115.121.1.15)
Examples	schacUserPresenceID = xmpp:pepe@im.univx.es schacUserPresenceID = sip:pepe@myweb.com schacUserPresenceID = sip:+34-95-505-6600@univx.es;transport=TCP;user=phone schacUserPresenceID = sips:alice@atlanta.com?subject=project%20x&priority=urgent schacUserPresenceID = h323:pepe@myweb.fi:808;params

4.3 Student Information

Student information includes attributes that have relevance to the student role, such as curriculum, major, and degree.

No attributes defined.

4.4 Employee Information

Employee information includes attributes that have relevance to the employee role, such as position, office hours, and job title

4.4.1 schacPersonalPosition

Name	schacPersonalPosition
Description	The Personal Position attribute type specifies a personal position inside an institution.
Format	urn:mace:terena.org:schac:personalPosition:<iNSS> <ul style="list-style-type: none"> ● <iNSS> is a Namespace Specific String as defined in RFC 2141 but case insensitive. Valid components for it are those specified (or explicitly delegated) by the TERENA URN Registry for this attribute at http://www.terena.nl/registry/terena.org/schac/personalPosition
# of values	Multi
RFC 2252 definition	(schacAttributeType:13 NAME 'schacPersonalPosition' DESC 'Position inside an institution' EQUALITY caseIgnoreMatch SUBSTR caseIgnoreSubstringsMatch SYNTAX 1.3.6.1.4.1.1466.115.121.1.15)
References	<ul style="list-style-type: none"> ● RFC 2141 - URN Syntax ● TERENA URN Registry: http://www.terena.nl/registry/terena.org/ ● RFC 2256 - A Summary of the X.500(96) User Schema for use with LDAPv3. Section: 5.13 title This attribute contains the title, such as "Vice President", of a person in their organizational context. The "personalTitle" attribute would be used for a person's title independent of their job function.
Examples	schacPersonalPosition = urn:mace:terena.org:schac:personalPosition:umk.pl:programmer

4.5 Linkage Identifiers / Foreign Keys

Linkage attributes are those identifiers used to link a directory entry with records in external data stores or other directory entries. The use of linkage identifiers can obviate the need to synchronize data elements between systems of record and the enterprise directory. Linkage attributes are also used in the implementation of metadirectory services.

4.5.1 schacPersonalUniqueCode

Name	schacPersonalUniqueCode
Description	Specifies a "unique code" for the subject it is associated with. Its value does not necessarily correspond to any identifier outside the scope of the directories using this schema. This might be Student number, Employee number,...
Format	urn:mace:terena.org:schac::personalPublicUniqueID:<country-code>:<iNSS> <ul style="list-style-type: none"> ● The <country-code> must be a valid two-letter ISO 3166 country code identifier, and assigned by the TERENA URN Registry for this attribute at http://www.terena.nl/registry/terena.org/schac/personalPublicUniqueID ● <iNSS> is a Namespace Specific String as defined in RFC 2141 but case insensitive, from a nationally controlled vocabulary, published through the URI identified at the above mentioned TERENA URN registry.
# of values	Multi
References	<ul style="list-style-type: none"> ● RFC 2141 - URN Syntax ● ISO 3166 - Codes for the representation of names of countries and their subdivisions ● TERENA URN Registry: http://www.terena.nl/registry/terena.org/ ● HEP rev 06 - Nov 21, 2005 (6.5.2 Student System Identification Code) http://middleware.internet2.edu/dir/docs/draft-internet2-mace-dir-higher-ed-person-analysis-latest.htm
RFC 2252 definition	(schacAttributeType:14 NAME 'schacPersonalUniqueCode' DESC 'Unique code for the subject' EQUALITY caseIgnoreMatch ORDERING caseIgnoreOrderingMatch SUBSTR caseIgnoreSubstringsMatch SYNTAX 1.3.6.1.4.1.1466.115.121.1.15)
Examples	schacPersonalUniqueCode = urn:mace:terena.org:schac:personalPublicUniqueCode:fi:tut.fi:student:165934 schacPersonalUniqueCode = urn:mace:terena.org:schac:personalPublicUniqueCode:es:uma:estudiante:a3b123c12 schacPersonalUniqueCode = urn:mace:terena.org:schac::personalPublicUniqueCode:se:LIN:87654321

4.5.2 schacPersonalUniqueID

Name	schacPersonalUniqueID
Description	Specifies a "legal unique identifier" for the subject it is associated with. This might be DNI in Spain, FIC in Finland, NIN in Sweden,...
Format	urn:mace:terena.org:schac:personalUniqueID:<country-code>:<idType>:<idValue> <ul style="list-style-type: none"> ● The <country-code> must be a valid two-letter ISO 3166 country code identifier, and assigned by the TERENA URN Registry for this attribute at http://www.terena.nl/registry/terena.org/schac/personalUniqueID ● <idType>. Acceptable values must be declared per each country code through the URI identified at the above mentioned TERENA URN registry. ● <idValue>
# of values	Multi
References	<ul style="list-style-type: none"> ● RFC 2141 - URN Syntax ● ISO 3166 - Codes for the representation of names of countries and their subdivisions ● TERENA URN Registry: http://www.terena.nl/registry/terena.org/
RFC 2252 definition	(schacAttributeType:15 NAME 'schacPersonalUniqueID' DESC 'Unique code for the subject' EQUALITY caseExactMatch ORDERING caseExactOrderingMatch SUBSTR caseExactSubstringsMatch SYNTAX 1.3.6.1.4.1.1466.115.121.1.15)
Examples	schacPersonalUniqueID = urn:mace:terena.org:schac:personalUniqueID:es:NIF:31241312L schacPersonalUniqueID = urn:mace:terena.org:schac:personalUniqueID:fi:FIC:260667-123F schacPersonalUniqueID = urn:mace:terena.org:schac:personalUniqueID:se:NIN:12345678

4.5.3 schacUUID

Name	schacUUID
Description	Specifies a "universally unique identifier" for an entity representing a person.
Format	<UUID> <ul style="list-style-type: none"> ● <UUID>. A UUID is essentially a 16-byte number and in its canonical form a UUID may look like this: f81d4fae-7dec-11d0-a765-00a0c91e6bf6. UUID generation requires no central registration process
# of values	Single
References	<ul style="list-style-type: none"> ● draft-zeilenga-ldap-uuid-06.txt - The LDAP entryUUID operational attribute
RFC 2252 definition	(schacAttributeType:16 NAME 'schacUUID' DESC 'UUID for the entity' EQUALITY uuidMatch ORDERING uuidOrderingMatch SYNTAX { uuid-IANA-ASSIGNED-OID.1 })
Examples	schacUUID = f81d4fae-7dec-11d0-a765-00a0c91e6bf6

4.6 Entry Metadata / Administration Information

Entry metadata attributes are used to contain information about the entry itself, often its status, birth, and death. Such attributes can be critical to metadirectory processing. While the object classes discussed here were designed to accommodate person entries, metadata attributes can also be useful with non-person entry types such as groups. In such cases the metadata attributes may be best defined in an auxiliary object class independent of the person object class.

4.6.1 schacExpiryDate

Name	schacExpiryDate
Description	The date from which the set of data is to be considered invalid (specifically, in what refers to rights and entitlements). This date applies to the entry as a whole.
Format	Values MUST be expressed Greenwich Mean Time (Zulu) and MUST include seconds (i.e., times are YYYYMMDDhhmmssZ), even where the number of seconds is zero. GeneralizedTime values MUST NOT include fractional seconds.
# of values	Single
References	<ul style="list-style-type: none"> ● RFC 2630 - Cryptographic Message Syntax. Section 11.3 ● RFC 2985 - PKCS #9: Selected Object Classes and Attribute Types Version 2.0. Sections 5.2.4, B.3.8 ● RFC 3339 - Date and Time on the Internet: Timestamps. 'Date and Time on the Internet: Timestamps' as reference using the 'full-date' format from paragraph 5.6 but without the dashes ● ISO 8601 - Data elements and interchange formats - Information interchange - Representation of dates and times
RFC 2252 definition	(schacAttributeType:17 NAME 'schacExpiryDate' DESC 'Date from which the set of data is to be considered invalid (format YYYYMMDDhhmmssZ)' EQUALITY generalizedTimeMatch ORDERING generalizedTimeOrderingMatch SYNTAX 1.3.6.1.4.1.1466.115.121.1.24)
Examples	schacExpiryDate = 20051231125959Z

4.7 Security Attributes and Keys

Security attributes are used to assist in authentication-related activities such as password self-reset. Security attributes that contain sensitive data such as passwords should be carefully protected, highly restricted, and probably encrypted using a one-way hash algorithm such as MD5 or SHA1 so that in the event that the directory server is compromised in an attack the attribute values are not useful to an attacker.

No attributes defined.

4.8 Confidentiality / Attribute Release (Visibility)

Confidentiality attributes are commonly used to indicate whether an entry is visible publicly, visible only to affiliates of the institution, or not visible at all. In some cases only specific attributes, such as phone, address, and email address, are restricted, in other cases all attributes are restricted.

4.8.1 schacUserPrivateAttribute

Name	schacUserPrivateAttribute
Description	Used to model privacy requirements, as expressed by the user and/or the organizational policies. The values are intended to be attribute type names and applies to the attribute and any subtypes of it for a given entity. In what respects to data exchange, it applies to the expression of privacy requirements. This attribute can also have specific operational semantics (one has already been applied to LDAP servers: see references below), that will be defined in a separate document.
Format	An attribute type identifier. Operational semantics may imply specific values as wildcards.
# of values	Multi
References	<ul style="list-style-type: none"> ● http://www.rediris.es/ldap/doc/irisUserPrivateAttribute/tnc2005-irisUserPrivateAttribute.pdf
RFC 2252 definition	(schacAttributeType:18 NAME 'schacUserPrivateAttribute' DESC 'Set of denied access attributes' EQUALITY caseIgnoreIA5Match SUBSTR caseIgnoreIA5SubstringsMatch SYNTAX 1.3.6.1.4.1.1466.115.121.1.26)
Examples	<ul style="list-style-type: none"> ● Attributes mail and telephoneNumber are considered private schacUserPrivateAttribute = mail schacUserPrivateAttribute = telephoneNumber

4.9 Authorization, Entitlements

Authorization for services is generally implemented in LDAP directories either through the use of entry attributes or group memberships. (For information regarding LDAP groups please see the [MACE Best Practices for Directory Groups](#) document at <http://middleware.internet2.edu/dir/groups>).

Applications such as [Shibboleth](#) (see <http://shibboleth.internet2.edu>) can make use of entitlement attributes in an entry to provide authorization information to requesting services.

4.9.1 schacUserStatus

Name	schacUserStatus
Description	Used to store a set of status of a person as user of services
Format	urn:mace:terena.org:schac:status:<iNSS> <ul style="list-style-type: none"> ● <iNSS> is a Namespace Specific String as defined in RFC 2141 but case insensitive
# of values	Multi
References	<ul style="list-style-type: none"> ● RFC 2141 - URN Syntax
RFC 2252 definition	(schacAttributeType:19 NAME 'schacUserStatus' DESC 'Used to store a set of status of a person as user of services' EQUALITY caseIgnoreMatch SUBSTR caseIgnoreSubstringsMatch SYNTAX 1.3.6.1.4.1.1466.115.121.1.15)
Examples	<ul style="list-style-type: none"> ● To store different user activity states at University of Málaga (uma.es): schacUserStaus = urn:mace:terena.org:schac:status:uma.es:affiliation:expired schacUserStaus = urn:mace:terena.org:schac:status:uma.es:sendMail:expired schacUserStaus = urn:mace:terena.org:schac:status:uma.es:getMail:active ● A parameter in the URN can be used to represent the temporal validity of the satus: schacUserStatus = urn:mace:terena.org:schac:status:ujl.si:webmail:active?ttl=20060531235959

4.10 Group-related Attributes

Directory groups are often used to provide authorization to entries and attributes, as well as to restrict or provide access to services. There are benefits to having group memberships described in members' entries as well as in a group entry. Because not all DSA's provide this functionality (Microsoft Active Directory and Novell eDirectory do) local attributes are often defined to meet organizational needs. For a complete treatment of issues concerning LDAP groups please see the [MACE Best Practices for Directory Groups](http://middleware.internet2.edu/dir/groups) document at <<http://middleware.internet2.edu/dir/groups>>

No attributes defined.

A Appendices

A.1 SCHAC LDAP Schema

Definitions of the object class and attribute types specified in this document have been done in accordance with RFC 2252, in an attempt to ease integration with LDAP-accessible Directory systems. Lines have been folded in some cases to improve readability.

A.1.1 Object identifiers

```
objectIdentifier TERENA 1.3.6.1.4.1.25178

objectIdentifier schac TERENA:1
objectIdentifier schacObjectClass schac:1
objectIdentifier schacAttributeType schac:2
```

A.1.2 Object classes

A.1.2.1 schacPersonalCharacteristics

```
(
  schacObjectClass:1
  NAME 'schacPersonalCharacteristics'
  DESC 'Personal characteristics describe the individual person
        represented by the entry'
  AUXILIARY
  MAY (
    schacMotherTongue $ schacGender $ schacDateOfBirth $
    schacPlaceOfBirth $ schacCountryOfCitizenship $
    schacSn1 $ schacSn2 $ schacPersonalTitle
  )
)
```

A.1.2.2 schacContactLocation

```
(
  schacObjectClass:2
  NAME 'schacContactLocation'
  DESC 'Primary means of locating and contacting potential
        collaborators and other persons-of-interest at peer
        institutions'
  AUXILIARY
  MAY (
    schacHomeOrganization $ schacHomeOrganizationType $
    schacCountryOfResidence $ schacUserPresenceID
  )
)
```

A.1.2.3 schacEmployeeInfo

```
(
  schacObjectClass:3
  NAME 'schacEmployeeInfo'
  DESC 'Employee information includes attributes that have
        relevance to the employee role, such as position, office
        hours, and job title'
  AUXILIARY
  MAY ( schacPersonalPosition )
)
```

A.1.2.4 schacLinkageIdentifiers

```
(
  schacObjectClass:4
  NAME 'schacLinkageIdentifiers'
  DESC 'Used to link a directory entry with records in external
        data stores or other directory entries'
  AUXILIARY
  MAY (
    schacPersonalUniqueCode $ schacPersonalUniqueID $ schacUUID
  )
)
```

A.1.2.5 schacEntryMetadata

```
(
  schacObjectClass:5
  NAME 'schacEntryMetadata'
  DESC 'Used to contain information about the entry itself, often
        its status, birth, and death'
  AUXILIARY
  MAY (
    schacExpiryDate
  )
)
```

A.1.2.6 schacEntryConfidentiality

```
(
  schacObjectClass:6
  NAME 'schacEntryConfidentiality'
  DESC 'Used to indicate whether an entry is visible publicly,
        visible only to affiliates of the institution, or not
        visible at all'
  AUXILIARY
  MAY (
    schacUserPrivateAttribute
  )
)
```

A.1.2.7 schacUserEntitlements

```
(
  schacObjectClass:7
  NAME 'schacUserEntitlements'
  DESC 'Authorization for services'
  AUXILIARY
  MAY (
    schacUserStatus
  )
)
```

A.1.3 Attribute types

A.1.3.1 schacMotherTongue

```
(
  schacAttributeType:1
  NAME 'schacMotherTongue'
  DESC 'RFC 3066 code for preferred language of communication'
  EQUALITY caseExactMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15
)
```

A.1.3.2 schacGender

```
(
  schacAttributeType:2
  NAME 'schacGender'
  DESC 'Representation of human sex (see ISO 5218)'
  EQUALITY integerMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.27
)
```

A.1.3.3 schacDateOfBirth

```
(
  schacAttributeType:3
  NAME 'schacDateOfBirth'
  DESC 'Date of birth (format YYYYMMDD, only numeric chars)'
  EQUALITY numericStringMatch
  ORDERING numericStringOrderingMatch
  SUBSTR numericStringSubstringsMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.36
)
```

A.1.3.4 schacPlaceOfBirth

```
(
  schacAttributeType:4
  NAME 'schacPlaceOfBirth'
  DESC 'Birth place of a person'
  EQUALITY caseIgnoreMatch
  ORDERING caseIgnoreOrderingMatch
  SUBSTR caseIgnoreSubstringsMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15
)
```

A.1.3.5 schacCountryOfCitizenship

```
(
  schacAttributeType:5
  NAME 'schacCountryOfCitizenship'
  DESC 'Country of citizenship of a person. Format two-letter
        acronym according to ISO 3166'
  EQUALITY caseIgnoreMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15
)
```

A.1.3.6 schacSn1

```
(
  schacAttributeType:6
  NAME 'schacSn1'
  DESC 'First surname of a person'
  EQUALITY caseIgnoreMatch
  ORDERING caseIgnoreOrderingMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15
)
```

A.1.3.7 schacSn2

```
(
  schacAttributeType:7
  NAME 'schacSn2'
  DESC 'Second surname of a person'
  EQUALITY caseIgnoreMatch
  ORDERING caseIgnoreOrderingMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15
)
```

A.1.3.8 schacPersonalTitle

```
(
  schacAttributeType:8
  NAME 'schacPersonalTitle'
  DESC 'RFC1274: personal title'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15
)
```

A.1.3.9 schacHomeOrganization

```
(
  schacAttributeType:9
  NAME 'schacHomeOrganization'
  DESC 'Domain name of the home organization'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.26
)
```

A.1.3.10 schacHomeOrganizationType

```
(
  schacAttributeType:10
  NAME 'schacHomeOrganizationType'
  DESC 'Type of the home organization'
  EQUALITY caseIgnoreMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15
)
```

A.1.3.11 schacCountryOfResidence

```
(
  schacAttributeType:11
  NAME 'schacCountryOfResidence'
  DESC 'Country of citizenship of a person. Format two-letter
        acronym according to ISO 3166'
  EQUALITY caseIgnoreMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15
)
```

A.1.3.12 schacUserPresenceID

```
(
  schacAttributeType:12
  NAME 'schacUserPresenceID'
  DESC 'Used to store a set of values related to the network
        presence'
  EQUALITY caseExactMatch
  SUBSTR caseExactSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15
)
```

A.1.3.13 schacPersonalPosition

```
(
  schacAttributeType:13
  NAME 'schacPersonalPosition'
  DESC 'Position inside an institution'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15
)
```

A.1.3.14 schacPersonalUniqueCode

```
(
  schacAttributeType:14
  NAME 'schacPersonalUniqueCode'
  DESC 'Unique code for the subject'
  EQUALITY caseIgnoreMatch
  ORDERING caseIgnoreOrderingMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15
)
```

A.1.3.15 schacPersonalUniqueID

```
(
  schacAttributeType:15
  NAME 'schacPersonalUniqueID'
  DESC 'Unique code for the subject'
  EQUALITY caseExactMatch
  ORDERING caseExactOrderingMatch
  SUBSTR caseExactSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15
)
```

A.1.3.16 schacUUID

```
(
    schacAttributeType:16
    NAME 'schacUUID'
    DESC 'UUID for the entity'
    EQUALITY uuidMatch
    ORDERING uuidOrderingMatch
    SYNTAX {uuid-IANA-ASSIGNED-OID.1}
)
```

A.1.3.17 schacExpiryDate

```
(
    schacAttributeType:17
    NAME 'schacExpiryDate'
    DESC 'Date from which the set of data is to be considered
         invalid (format YYYYMMDDhhmmssZ)'
    EQUALITY generalizedTimeMatch
    ORDERING generalizedTimeOrderingMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.24
)
```

A.1.3.18 schacUserPrivateAttribute

```
(
    schacAttributeType:18
    NAME 'schacUserPrivateAttribute'
    DESC 'Set of denied access attributes'
    EQUALITY caseIgnoreIA5Match
    SUBSTR caseIgnoreIA5SubstringsMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.26
)
```

A.1.3.19 schacUserStatus

```
(
    schacAttributeType:19
    NAME 'schacUserStatus'
    DESC 'Used to store a set of status of a person as user of
         services'
    EQUALITY caseIgnoreMatch
    SUBSTR caseIgnoreSubstringsMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.15
)
```

B List of Changes

- May 4, 2006. V: 1.2.0.
Changed schacUserPresenceID syntax from URN to URI. Added references to the TERENA URN registry. Clarify schaExpiryDate scope.
- March 27, 2006. V: 1.1.2.
Added SCHACPREFIX URN. URN reserved for SCHAC: urn:mace:terena.org:schac:
- March 10, 2006. V: 1.1.1.
Added TERENA OID. Branch reserved for SCHAC: 1.3.6.1.4.1.25178.1
- February 10, 2006. V: 1.1.0.
Added appendix with LDAP schema.
- November 22, 2005. V: 1.0.0.
Added attribute's classification according to HEP categories.
- September 5, 2005. V: 1.0.0 RC3.
- June 24, 2005. V: 1.0.0 RC2.
- June 1, 2005. V: 1.0.0 RC1.
- May 24, 2005. V: 0.2.
- April 25, 2005. V: 0.1.